

Aluminium windows with ALU axxent PLUS and ALU safety opening restrictor



More information:

[ALU axxent PLUS product page](#)

ALU axxent PLUS turn-only element

- Fully concealed hinges: narrower profile views and larger glazed areas
- Load capacity of up to 130 kg when used in combination with the safety opening restrictor, certified for long-term, safe window operation
- Large opening angle of 110° in the turning position
- Non-corrosive materials ensure sustainably beautiful and resistant surfaces

Production benefits

- Quick and easy assembly: small number of clampable compact components with a high degree of pre-assembly for simpler installation
- Quick fabrication and assembly: continuous height and side adjustment, sash can also be installed on the building site

ALU safety opening restrictor

- Limiting restrictor to ensure the safety of children
- Fulfils special child-safety requirements in accordance with EN 13126-5 Class 5/6
- Slim opening width <89 mm (depending on system)
- Two restrictors used per sash
- Integrated anti-slam device in ventilation position
- Authorised individuals can disengage the restrictor using the lockable handle with tilt-before-turn function (in 180° handle position)
- No additional, visible unlocking mechanism, giving the window a superior, unspoiled appearance
- Restrictors automatically engage again when the window is turned to the locking position
- Used for turn-only windows



Environmental performance analysis*

* LCA available, please contact us at nachhaltigkeit@siegenia.com.



More information:

[Function video](#)