


Aluminium windows with ALU 5200 and ALU comfort opening restrictor, RC2



 **More information:**
[ALU 5200 product page](#)

ALU 5200, RC2

- Sashes weighing up to 170 kg for safe, wear-resistant and convenient operation
- Narrow frame widths due to low window frame clearance
- Custom anodised or colour coating
- Non-corrosive materials ensure sustainably beautiful and resistant surfaces

Production benefits

- Quick and easy assembly: small number of clampable compact components with a high degree of pre-assembly for simpler installation
- Non-handed
- 3D adjustment for straightforward tolerance compensation
- Pre-assembled component system with an extensive range of accessories that can be used in any combination



Environmental
performance analysis*

* LCA available, please contact us at nachhaltigkeit@siegenia.com.

ALU comfort opening restrictor

- Limiting restrictor for comfort applications, e.g. comfort ventilation
- For applications without any special safety requirements
- Slim opening width <89 mm
- Corresponds to Class 5/1 in accordance with DIN EN 13126-5
- Quick and easy to disengage the restrictor by hand
- No additional, visible unlocking mechanism, giving the window a superior, unspoiled appearance
- The restrictor engages again automatically after the window sash is closed
- Released by manually unlatching the restrictor; engages automatically when the sash is closed
- Used for turn-only and turn-and-tilt windows

 **More information:**
[Function video](#)