

Aluminium sliding door: PORTAL HS ALU with SOFT CLOSE compact / SOFT STOP compact, locking bolt drive and smart window handle



SOFT CLOSE compact / SOFT STOP compact

- SOFT CLOSE brakes the sash, allowing it to automatically come to a stop in the end position
- SOFT STOP compact only brakes the sash if it moves too quickly shortly before the end position; the operator then pulls the sash to the end position with the usual amount of force
- Can be integrated in narrow profile systems
- No special guiding rail required for aluminium systems

Production benefits

- Can be scaled by weight
- Simple installation, no need to mill out sashes




* LCA available, please contact us at nachhaltigkeit@siegenia.com.

Locking bolt gear

- Elegant design thanks to flush strikers in the frame
- Depending on the profile systems, integration of the strikers into a locking rail

Production benefits

- Backsets 27.5 mm or 37.5 mm
- System with strikers and locking points on the gear
- Gear lengths up to 280 cm
- Comfort gear recommended for weights of 200 kg or more



Aluminium sliding door: PORTAL HS ALU with SOFT CLOSE compact / SOFT STOP compact, locking bolt drive and smart window handle



More information:

[Smart window handle product page](#)

Smart window handle



- Smart: lock and unlock without a key
- Secure: opening and locking monitoring system
- Practical: lots of smart features
- Intuitive: control via the app or using a voice assistant
- Combinable: with heating, lighting, etc.
- Compatible: Matter smart home standard
- Simple: configure via a QR code

Installation benefits

- Colours: white, anthracite
- For timber and PVC windows
- Installation similar to a manual window handle
- Variable spindle length: 32–42 mm
- Battery-operated



* LCA available, please contact us at nachhaltigkeit@siegenia.com.