

Aluminium door with BS 3700, daytime release, safety lock, A-opener and ALU axxent 750 door hinge



Automatic multi-point locking system BS 3700

- Automatic multi-point locking system with self-adjustment, no subsequent readjustment necessary on site
- Retaining elements fix the door sash securely in the frame parts at all times
- Free engagement at all times of all locking elements (2 x hook bolts and main lock bolt) with bolt back-pressure protection
- Automatic 20 mm projection of the hook bolt and main lock bolt with a backset of as little as 35 mm
- Child-proof lock activated by disabling the door handle using the cylinder lock

Production benefits

- DIN orientation can be adjusted using the main lock latch only
- Automatic trigger latch with self-adjustment of the DIN orientation
- Existing KfV AS 2xxx, BS 2xxx or AS 3xxx can be replaced with minimal effort
- Easy to retrofit the daytime release: when uninstalled by fixing with a screw at the side

Freely configurable options:

- Daytime release TA suitable for retrofitting
- Safety lock T3 with handle operation inside
- Safety lock T4 with handle operation inside and via the cylinder lock inside/outside
- Extension pieces for doors up to 3 m in height
- A-opener for electromechanical opening of the door
- Control possible via SIEGENIA access control systems: fingerprint scanner, keypad and transponder
- IO module smart for connection to existing third-party systems



Environmental performance analysis*

* LCA available, please contact us at nachhaltigkeit@siegenia.com.

Aluminium door with BS 3700, daytime release, safety lock, A-opener and ALU axxent 750 door hinge



ALU axxent 750 door hinge

- Concealed technology for a high-quality design
- Heavy door sash weighing up to 180 kg
- Burglar resistance RC2 as per EN 1627
- Contemporary look: available in silver (RAL 9006 white aluminium) and on-trend black (RAL 9005 jet black)
- No accumulation of dirt thanks to concealed technology
- Extremely easy to use: door sash turns smoothly thanks to a low-friction door hinge bearing

Production benefits

- Quick and easy to install thanks to "click in" technology
- Simple to adjust: adjustment elements fully integrated in the sash component
- Automated installation of the door hinges thanks to the self-tapping screws